

3000VA/1800W LINE INTERACTIVE UPS

S-U3000



Protection
Overload, Short circuit
Over Discharge & Charge



24V DC
Battery Voltage



120 Min*
Backup



8 Hrs*
Recharge Time

Specification

PF	0.6
Input	
Voltage	220-240VAC
Voltage Range	140-300VAC
Nominal Input Frequency	50/60Hz
Input Type	IEC C20
Input Breaker	YES
Output	
Output Voltage	220-240VAC
Ac Voltage Regulation (Battery Mode)	230VAC+/-10%
Frequency Range (Battery Mode)	50/60±1 Hz (default 50Hz)
Transfer Time	4ms typical
Waveform (Battery Mode)	Simulated Sine-wave
Outlet	UK*4
Current Crest Ratio	3:1
Full protection	Overload, short circuit, over discharger and over charger
Line/AVR/Battery Mode Overload	>(110%±10)% fault after alarm 1min, >(120%±10)% fault immediately, <90% go back
Efficiency	
Efficiency (Line Mode)	>95%
Efficiency (AVR Mode)	>92%
Efficiency (Battery Mode)	>65%
GP/Energy Star meet	YES
Battery	
Battery Voltage	24V DC
Battery Type & Number	4*12V7AH
Charging Current	2.0A±.2A
Recharge Time to 90% (Stand Model)	8 HOURS
Indicators	
Display	LCD display
Alarm	Battery mode: Sounding every 30 seconds, Low Battery: Sounding every 2 seconds, Over Load: Sounding every 0.5 seconds, Fault: Continuous Sounding
Interface	
USB(HID) & RJ45/RJ11(TVSS)	Yes
Physical	
Dimension & Net Weight	151 x 225 x 390 (W * H * D)(mm) & 18.1 (kgs)
Environment	
Humidity and Temperature	10 to 90%, 0 to 40°C
Noise Level	Less than 50 dB



www.secureye.com